

DIAMOND *flexos*

Fiber Optic Active Components

19" SWITCHES

The Fast Ethernet WebSmart switches are noted for the simplicity of an unmanaged switch, but they still come with reliable web-based management.

ADVANTAGES

- ▶ Ideal for small companies due to being cost-effective
- ▶ Standalone or 19" rack version
- ▶ Plug & play
- ▶ User-friendly management thanks to a graphical user interface (GUI)
- ▶ No disturbing noises
- ▶ No encoded SFPs (small form-factor pluggables)
- ▶ 5-year guarantee following registration at www.alliedtelesis.com

FEATURES

- ▶ 16x or 24x 10/100Base-TX RJ-45
- ▶ 2x uplink 1000Base-T SFP combo ports
- ▶ VLAN (802.1Q, MAC-based, port-based), QoS (Quality of Service), STP/RSTP/MSTP (802.1d/w/s), IGMP snooping (v1/v2), link aggregation (802.3ad), authentication (802.1x)
- ▶ Web-based management
- ▶ Passive cooling
- ▶ Non-blocking system

TECHNICAL SPECIFICATIONS

Model:	19" Fast Ethernet WebSmart switch
Connections:	16x or 24x 10/100Base-TX RJ-45 2x uplink 1000Base-T SFP combo ports
Functions:	IEEE 802.3x Flow control IEEE 802.1p Prioritisation IEEE 802.1x Authentication IEEE 802.1d Bridging IEEE 802.3ad Link aggregation IEEE 802.1Q Tagged VLAN IEEE 802.1d/w Spanning tree / rapid spanning tree
Power supply:	100–240 V AC, 50 / 60Hz
Housing dimensions:	16 ports: 35.2 x 25.6 x 4.32 cm (L x W x H) 24 ports: 44 x 25.7 x 4.32 cm (L x W x H)
Operating temperature:	0 to 45
Storage temperature:	-20 to 70
Relative humidity:	5% to 90% non-condensing

WebSmart FE Switch

Fast Ethernet



DIAMOND SA • Via dei Patrizi 5 • CH-6616 Losone • Switzerland
Tel. +41 91 785 45 45 • Fax +41 91 785 45 00 • e-mail info@diamond-fo.com

www.diamond-fo.com

Specifications subject to change without notice

BDD 1951470_03_13

ORDERING INFORMATION

SHORT DESCRIPTION	DESCRIPTION	ORDER NUMBER
19" 16-port FE Web-Smart switch	19" Fast Ethernet WebSmart switch with 16x 10/100Base-TX and 2x uplink 1000Base-T SFP combo ports Model: AT-FS750/16	EQQ 1065366
19" 24-port FE Web-Smart switch	19" Fast Ethernet WebSmart switch with 24x 10/100Base-TX and 2x uplink 1000Base-T SFP combo ports Model: AT-FS750/24	EQQ 1065357